

datasheet


Electric strike 9334VGL10



Electric strike 9334VGL10

Compact, functional design, modern environment-neutral design in aluminium. Surface of the counter plate with 6 mm adjustment facility.

In all-glass doors, particularly those with additional fanlight and glass side panels, the particular benefits of this strike are brought to bear: Trouble-free mounting as well as a compact and outstandingly functional design. No complex mounting fixtures required for installation - simply glue on (special adhesive is provided with each strike). The aluminium masonry box is available for two strike types: fail locked and fail unlocked configurations. Modern, environment-neutral design of the strike set, which consists of the strike itself and an identically dimensioned mating component.



		Glasstärke						
		8	9	10	11	12	13	15
Variable Maße	A	5	4,5	4	3,5	3	2,5	2
	B	8,1	9,1	10,1	11,1	12,1	13,1	15,1

Overview of Advantages

- Can be mounted DIN right or left by turning over 180°

Scope of delivery

-

technical data	
Voltage	12 V DC
Fail-unlocked	Yes
Glas door thickness	10 mm
Break-in resistance	6500 N
Height	145 mm
Depth	13 mm
Width	45 mm
Operating temperature range	-15 °C to +40 °C
Installation position	vertical and horizontal
Operating voltage tolerance range	± 1 V
Rated resistance	62,00 Ω
DC current consumption (50% Residual ripple)	185 mA
Current consumption DC (stabilised)	195 mA
DC-operating noise	no noise [0]
Max. latch preload DC (50 ripple)	10 N
EAN-Number	
4042203143128	Article number
	9334VGL10---E91